



Skyle (Remote Eyetracker Device) Technical Specifications

Sampling rate	20 Hz (max. 40Hz)
Accuracy	1° - 2° (better accuracy planned)
Eye tracking mode	Both eyes
Operating distance	45 - 65cm
Tracking Range (Width x Height)	30 x 12cm
Tracking Method	Dark pupil, binocular tracking
Calibration points	9
Data connection	USB 3.0 (more on demand)
Illuminators	NIR 850nm
Eyewear compatibility	Glasses planned - works with contact lenses
Dimensions	200 x 42,5 x 44mm (l*w*h)
Data provided	Timestamp, gaze coordinates (more on demand)
API Language	C#

System

OS Compatibility	Platform independent (currently only Windows)
Display size	Max. 24"
CPU Load	2% (Core i7)

eyeV GmbH reserves the right to make modifications, improvements, corrections or other changes without further notice to this document and any product described herein.

eyeV GmbH products are specifically not authorized for use as critical components in life support devices or applications, where the use can be reasonably expected to result in significant injury to the user.

Skyle is only available to B2B customers with a valid VAT number.

Published by eyeV GmbH
Alzeyer-Straße. 39, D-67549 Worms
www.eyev.de © 2019 eyeV GmbH. All rights reserved.